POWER 4 W CHARACTERISTIC 50 Q	APPLICAB	LE STAND	ARD									
COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED RX MON CONTROL RX MANUAL RX MON CONTROL RX MANUAL RX MON CONTROL RX MANUAL RX MA				4 167		1			50 Ω			
RATING	RATING	TEMPERATURE RANGE		1000 TO 105 00		STORA	GE			5 °C		
REGULENCY DC TO 6 GHz				-40 C 1O +8	J (EMPE	KATURE RA	NGE				
PANGE DC TO 6 GHz						ADDI ICADI E CADI E		_				
REANGE		RANGE OPERATING HUMIDITY		DC TO 6 GHz					1.5D-HQEV	1.5D-HQEW		
TIEM				TO 90 %			ECTOR		HRM-J,MS-162-C	-J,MS-162-C(LP)-1		
CONSTRUCTION SENERAL VISUALLY AND BY MEASURING SENERAL SEMINATION INSTRUMENT. ELECTRIC CHARACTERISTICS V. W. R. FREQUENCY DC TO 3 GHz FREQUENCY 3 TO 6 GHz OUTER 180 mΩ MAX. SESISTANCE VALUE AT MAXIMUM OF DC 100ma. CENTER 180 mΩ MAX. V. SURSISTANCE OUTER 150 mΩ MAX. V. SURSISTANCE VALUE AT MAXIMUM OF DC 100ma. CENTER 150 mΩ MAX. V. SURSISTANCE VALUE AT DC 100V. ESISTANCE VOLTAGE PROOF MUST KEEP THE AC 100 V FOR 1 min. NO FLASHOVER OR BREAKDOWN. WECHANICAL CHARACTERISTICS DURABILITY 12000 TIMES INSERTION AND EXTRACTIONS SHALL BE DONE. SHALL BE DONE. COUTER 180 mΩ MAX OUTER 150 mΩ MAX COUTER 150 mΩ MAX OUTER 150 mΩ MAX COUTER 150 mΩ MAX COUTER 150 mΩ MAX OUTER 150 mΩ MAX COUTER			SPECIFICATION SPECIFICATION				 S	•				
SENERAL VISUALLY AND BY MEASURING NSTRUMENT. NST	ITEM		·				REQUIREMENTS				АТ	
ELECTRIC CHARACTERISTICS	CONSTR	UCTION										
SECONTACT ERISTICS	GENERAL					AC	ACCORDING TO DRAWING.				×	
SWR												
COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE					GHz.				1.4 MAX.			
OUTER 150 mΩ MAX. X X X X X X X X X	V.S.W.R.										_	
NSULATION VALUE AT DC 100V 1000 MΩ MIN. X VALUE AT DC 100V 1000 MΩ MIN. X VALUE AT DC 100V 1000 MΩ MIN. X VALUE AT DC 100V FOR 1 min. NO FLASHOVER OR BREAKDOWN X X VALUE AT DC 100V FOR 1 min. NO FLASHOVER OR BREAKDOWN X X VALUE AT DC 100V FOR 1 min. NO FLASHOVER OR BREAKDOWN X X VALUE AT DC 100V FOR 1 min. NO FLASHOVER OR BREAKDOWN X X VALUE AT DC 100V VALUE AT DC	CONTACT		VALUE AT MAXIMUM OF DC 100mA .							×	×	
COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE			VALUE AT DC 100V				001211 100 1112 111011				_	
MECHANICAL CHARACTERISTICS DURABILITY 12000 TIMES INSERTION AND EXTRACTIONS SHALL BE DONE. CENTER 180 mΩ MAX OUTER 150 mΩ MAX 2/NO DAMAGE CRACK AND LOOSENESS OF PARTS. CABLE TERMINATION STRENGTH TENSILE FORSE AT MAXIMUM 49 N IS APPLIED TO THE CABLE AXIALLY. DESIGNED COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE CHECKED DATE APPROVED KJ KANMANIARA OT. 06.2 CHECKED RZ. KANO OT. 06.2 DESIGNED CHECKED DATE CHECKED RZ. KANO OT. 06.2 DESIGNED VI. MATSSUD OT. 06.2 DRAWN VII. MATSSUD OT. 06.2 DRAWN VII. MATSSUD OT. 06.2 DRAWN VII. MATSSUD OT. 06.2 DRAWN SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350	RESISTANCE		VALUE AT DO 100V.				TOOU MILE MIN.			×	-	
DURABILITY 12000 TIMES INSERTION AND EXTRACTIONS SHALL BE DONE. DCONTACT RESISTANCE: CENTER 180 m2 MAX OUTER 150 m2 MAX QUICTR 150 m2 MAX	VOLTAGE PROOF		MUST KEEP THE AC 100 V FOR 1 min.			N	NO FLASHOVER OR BREAKDOWN.			×	×	
EXTRACTIONS SHALL BE DONE. CENTER 180 mQ MAX QUTER 150 mQ MAX QUTER 150 mQ MAX QUITER 150 mQ MAX QIND DAMAGE CRACK, AND LOOSENESS OF PARTS. CABLE HIST NOT BE LOOSEN OR BROKEN, Q NO DAMAGE AT THE CLAMP. COUNT DESCRIPTION OF REVISIONS DESIGNED DATE A REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED LIL KANAMURA APPROV	JECHAN	ICAL CHA	ARACT	ERISTICS								
SHALL BE DONE. QUITER 150 m\(\text{m}\) MAX QNO DAMAGE, CRACK, AND LOOSENESS OF PARTS. CABLE TERMINATION STRENGTH APPLIED TO THE CABLE AXIALLY. TENSILE FORSE AT MAXIMUM 49 N IS APPLIED TO THE CABLE AXIALLY. Q) NO DAMAGE AT THE CLAMP. COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE APPROVED K.J. KAWAMURA CHECKED RZ. KAMO 07. 06. 2 DESIGNED VIH. MATSUO 07. 0	DURABILITY											
©NO DAMAGE, CRACK, AND LOOSENESS OF PARTS. CABLE TERMINATION TENSILE FORSE AT MAXIMUM 49 N IS APPLIED TO THE CABLE AXIALLY. COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE APPROVED K.J. KANAMURA APPROVED CHECKED										_	l _	
TENSILE FORSE AT MAXIMUM 49 N IS APPLIED TO THE CABLE AXIALLY. COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE							②NO DAMAGE,CRACK,AND LOOSENESS OF PARTS.					
COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE \(\text{\text{\$\Delta}} \)												
COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE COUNT DESCRIPTION OF REVISIONS DESIGNED CHECKED DATE REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. CHECKED RZ. KANO 07. 06. 2: DESIGNED YH. MATSUO 07. 06. 2: DESIGNED YH. MATSUO 07. 06. 2: DRAWN STEATH OF THE CLAMP. SPECIFICATION SHEET PART NO. MS162L1—HRMJ—15W350						1	-				_	
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0	SINLINGIA		APPLIED TO THE CABLE AXIALLY.			(<u>2</u>)				^	_	
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350							1					
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA O7. 06. 2' CHECKED RZ. KANO O7. 06. 2' DESIGNED VH. MATSU0 O7. 06. 2' DRAWN Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0												
REMARK Lead-Free Solder(Sn3.0Ag0.5Cu) is used. APPROVED KJ. KAWAMURA 07. 06. 20 CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATSUO 0	COUNT	DES	CRIPTION	N OF REVISIONS	П	FSIGNE	L SIGNED		CHECKED DA'		L TF	
APPROVED KJ. KAWAMURA 07. 06. 29 CHECKED RZ. KANO 07. 06. 29 DESIGNED YH. MATSUO 07. 06. 29 D		+	. 2 1101						222			
Lead-Free Solder(Sn3.0Ag0.5Cu) is used. CHECKED RZ. KANO 07. 06. 20 DESIGNED YH. MATSUO 07. 06. 20 DRAWN YH. MATS	REMARK					APPROVED		KJ. KAWAMURA	07. 0	6. 29		
Unless otherwise specified, refer to JIS C 5402. Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. BOT. 06. 20 DRAWN YH. MATSU0 07. 06. 20 DRAWING NO. ELC4–180704–00 DRAWING NO. MS162L1–HRMJ–15W350	₋ead-Free	Solder(Sn3	.0Ag0.5	5Cu) is used.						07. 06. 29		
Note QT:Qualification Test AT:Assurance Test X:Applicable Test DRAWING NO. ELC4-180704-00 SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350							DESIGNED		YH. MATSUO	07. 06. 29		
SPECIFICATION SHEET PART NO. MS162L1-HRMJ-15W350	Unless otherwise specified, refer to JIS C 5402.						DRAWN		YH. MATSUO	07. 06. 29		
10 STESTIFICATION STILL!	Note QT:Qualification Test AT:Assurance Test X:Applicable Test D					DRAV	WING NO.		ELC4-180704	ELC4-180704-00		
	HRS	SPI	PECIFICATION SHEET			PART NO.		MS	S162L1-HRMJ-15W350			
OPM HD0011-2-1			SE ELECTRIC CO., LTD.			ODE NO. CL36		L362	2-0130-7-00		1/1	