

## Specification Sheet

Part Number: 155-03800



Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.7-6.0mm/ PA66HIRHS; Black; 500/Pack

<b>Article Number</b>	155-03800
<b>Type</b>	FT6LG-AMP
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Head design contains clamping rails to provide full circumferential compression around bundles.</li><li>•Bent tail allows for quick insertion into head.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
<b>Short Description</b>	Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.7-6.0mm/ PA66HIRHS; Black; 500/Pack

**Global Part Name**

FT6LG-AMP-PA66HIRHS-BK

**Fixation Method**

Fir Tree

**Panel Thickness Min(Imperial)**

0.028

**Panel Thickness Max(Imperial)**

0.24

**Panel Thickness Min (Metric)**

0.7

**Panel Thickness Max (Metric)**

6.0

**Mounting Hole Diameter D (Imperial)**

0.26 - 0.28

**Mounting Hole Diameter D (Metric)**

6.5 - 7.0 mm

**Mounting Hole Diameter D Min (Imperial)**

0.26

**Mounting Hole Diameter D Max (Imperial)**

0.28

**Mounting Hole Diameter D Max (Metric)**

7.0

**Disc Diameter(Metric)**

16.0

**Disc Diameter (Imperial)**

0.63

**Material**

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

**Material Shortcut**

PA66HIRHS

<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	0.88