



#### General ordering data

Order No.	0170720000
Part designation	SAKG 54 II
Version	Special terminal, special connections, 240 mm <sup>2</sup> , Screw connection, KrG, Medium yellow, TS 32
EAN	4008190064044
Qty.	5 pc(s).

#### Product notes

Note, technical data	Conductor connection with cable lugs according to DIN 46234 and DIN 46235, from 70 .. 240 mm <sup>2</sup>
----------------------	---

#### Additional technical data

Colour of insulating material	Medium yellow
Connection direction	on side
End plate required	Yes
Explosion-tested version "Ex e"	No
Installation advice	TS 32
Insulating material	KrG
Levels cross-connected internally	No
No. of identical terminals	1
No. of levels	1
No. of terminal strips per level	2
Open sides	Open
Operating temperature range	- 60 °C, + 130 °C
Product family	SAK Series
Type of connection	Screwed
Type of mounting	Snap-on
UL 94 flammability rating of insulation material	5VA
Version	Stud terminal

#### CSA rating data

Voltage (CSA)	600 V
CSA current	600 A
Min. cross-section (CSA)	kcmil 300
Max. cross-section (CSA)	kcmil 500

#### Conductors for clamping (rated connection)

Clamping range, min.	10 mm <sup>2</sup>
Clamping range, max.	240 mm <sup>2</sup>
Type of connection	Screw connection
2nd type of connection	screwed
Connection direction	on side

#### Conductors for clamping (rated connection)

No. of connections	1
Clamping screw	M 16
Tightening torque range	25...60 Nm
AWG conductor size, min.	kcmil 300
AWG conductor size, max.	kcmil 500
AWG conductor size, min.	150 mm <sup>2</sup>
AWG conductor size, max.	253.35 mm <sup>2</sup>

#### Dimensions

Width	54 mm
Height of lowest version	60.5 mm
Length	122 mm
Weight	591 g
TS 32 offset	61 mm

#### Rating data

Rated cross-section	240 mm <sup>2</sup>
Rated voltage	1,000 V
Rated impulse voltage	8 kV
Rated current	415 A
Standards	IEC 60947-7-1
Current with max. conductor	415 A
Pollution severity	3

#### UL rating data

Voltage (UL)	600 V
Current (UL)	380 A
Min. cross-section (UL)	kcmil 300
Max. cross-section (UL)	kcmil 500

#### Approvals

Approvals institutes



#### Downloads

STEP	0170720000_01122_SAKG_54_II_STP.stp
------	-------------------------------------

#### Classifications

ETIM 2.0	EC000897
ETIM 3.0	EC000897
eClass 4.1	27-14-11-31
eClass 5.0	27-14-11-31
eClass 5.1	27-14-11-31

### Similar products

Order No.	Part designation	Version
0185420000	SAKG 54 II/GW	Special terminal, special connections, 240 mm <sup>2</sup> , Screw connection, KrG, Medium yellow, TS 32