



PowerMESH™ IGBT, S series 600 V, 13 A low drop

Datasheet - production data



TO-220FP

Figure 1: Internal schematic diagram



SC12650

Features

- Low on-voltage drop ($V_{CE(sat)}$)
- High current capability

Applications

- Light dimmer
- Static relays
- Motor control

Description

Using the latest high voltage technology based on a patented strip layout, STMicroelectronics has designed an advanced family of IGBTs, the PowerMESH™ IGBTs, with outstanding performance. The suffix "S" represents a series optimized to achieve minimum on-voltage drop for low frequency applications.

Table 1: Device summary

| Order code | Marking | Package | Packing |
|-------------|-----------|----------|---------|
| STGF20NB60S | GF20NB60S | TO-220FP | Tube |

Contents

| | | |
|----------|---|-----------|
| 1 | Electrical ratings | 3 |
| 2 | Electrical characteristics | 4 |
| | 2.1 Electrical characteristics (curves) | 6 |
| 3 | Test circuits | 9 |
| 4 | Package information | 10 |
| | 4.1 TO-220FP package information | 11 |
| 5 | Revision history | 13 |

1 Electrical ratings

Table 2: Absolute maximum ratings

| Symbol | Parameter | Value | Unit |
|----------------|---|------------|------|
| V_{CES} | Collector-emitter voltage ($V_{GE} = 0$ V) | 600 | V |
| V_{ECS} | Emitter-collector voltage ($V_{GE} = 0$ V) | -20 | V |
| V_{GE} | Gate-emitter voltage | ± 20 | V |
| I_C | Continuous collector current at $T_C = 25$ °C | 24 | A |
| | Continuous collector current at $T_C = 100$ °C | 13 | |
| I^{CL} | Turn-off latching current | 70 | A |
| $I_{CM}^{(1)}$ | Pulsed collector current | 70 | A |
| P_{TOT} | Total dissipation at $T_C = 25$ °C | 40 | W |
| V_{ISO} | Insulation withstand voltage (RMS) from all three leads to external heat sink ($t = 1$ s, $T_C = 25$ °C) | 2.5 | kV |
| T_{STG} | Storage temperature range | -55 to 150 | °C |
| T_J | Operating junction temperature | | |

Notes:

⁽¹⁾Pulse width limited by safe operating area.

Table 3: Thermal data

| Symbol | Parameter | Value | Unit |
|----------------|-------------------------------------|-------|------|
| $R_{thj-case}$ | Thermal resistance junction-case | 3.1 | °C/W |
| $R_{thj-amb}$ | Thermal resistance junction-ambient | 62.5 | |

2 Electrical characteristics

$T_C = 25\text{ °C}$ unless otherwise specified

Table 4: Static characteristics

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|---------------|--------------------------------------|--|------|------|-----------|---------------|
| $V_{(BR)CES}$ | Collector-emitter breakdown voltage | $V_{GE} = 0\text{ V}$, $I_C = 250\text{ }\mu\text{A}$ | 600 | | | V |
| $V_{(BR)ECS}$ | Emitter-collector breakdown voltage | $V_{GE} = 0\text{ V}$, $I_C = 10\text{ mA}$ | -20 | | | |
| I_{CES} | Collector cut-off current | $V_{GE} = 0\text{ V}$, $V_{CE} = 600\text{ V}$ | | | 10 | μA |
| | | $V_{GE} = 0\text{ V}$, $V_{CE} = 600\text{ V}$, $T_C = 125\text{ °C}$ | | | 100 | |
| I_{GES} | Gate-emitter leakage current | $V_{CE} = 0\text{ V}$, $V_{GE} = \pm 20\text{ V}$ | | | ± 100 | nA |
| $V_{GE(th)}$ | Gate threshold voltage | $V_{CE} = V_{GE}$, $I_C = 250\text{ }\mu\text{A}$ | 2.5 | | 5 | V |
| $V_{CE(sat)}$ | Collector-emitter saturation voltage | $V_{GE} = 15\text{ V}$, $I_C = 20\text{ A}$ | | 1.25 | 1.7 | V |
| | | $V_{GE} = 15\text{ V}$, $I_C = 20\text{ A}$, $T_J = 150\text{ °C}$ | | 1.2 | | |

Table 5: Dynamic characteristics

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|------------------------------|--|------|------|------|---------------|
| $g_{fs}^{(1)}$ | Forward transconductance | $V_{CE} = 10\text{ V}$, $I_C = 8\text{ A}$ | - | 20 | - | S |
| C_{ies} | Input capacitance | $V_{CE} = 25\text{ V}$, $f = 1\text{ MHz}$, $V_{GE} = 0\text{ V}$ | - | 1820 | - | μF |
| C_{oes} | Output capacitance | | - | 167 | - | |
| C_{res} | Reverse transfer capacitance | | - | 27 | - | |
| Q_g | Total gate charge | $V_{CC} = 480\text{ V}$, $I_C = 20\text{ A}$, $V_{GE} = 15\text{ V}$ (see Figure 17: "Gate charge test circuit") | - | 83 | 115 | nC |
| Q_{ge} | Gate-emitter charge | | - | 10 | - | |
| Q_{gc} | Gate-collector charge | | - | 27 | - | |

Notes:

⁽¹⁾Pulse duration= 300 μs , duty cycle 1.5 %

Table 6: Inductive load switching on characteristics

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|-----------------------|--|------|------|------|------------------|
| $t_{d(on)}$ | Turn-on delay time | $V_{CC} = 480\text{ V}$, $I_C = 20\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 100\text{ }\Omega$ (see Figure 16: "Test circuit for inductive load switching") | - | 92 | - | ns |
| t_r | Current rise time | | - | 70 | - | ns |
| $(di/dt)_{on}$ | Turn-on current slope | | - | 340 | - | A/ μs |
| $t_{d(on)}$ | Turn-on delay time | $V_{CC} = 480\text{ V}$, $I_C = 20\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 100\text{ }\Omega$, $T_J = 125\text{ °C}$ (see Figure 16: "Test circuit for inductive load switching") | - | 80 | - | ns |
| t_r | Current rise time | | - | 73 | - | ns |
| $(di/dt)_{on}$ | Turn-on current slope | | - | 320 | - | A/ μs |

Table 7: Inductive load switching off characteristics

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|----------------|-----------------------|--|------|------|------|------|
| t_c | Cross-over time | $V_{CC} = 480\text{ V}$, $I_C = 20\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 100\ \Omega$ (see Figure 16: "Test circuit for inductive load switching") | - | 1.6 | - | ns |
| $t_r(V_{off})$ | Off voltage rise time | | - | 0.8 | - | |
| $t_{d(off)}$ | Turn-off delay time | | - | 1.1 | - | |
| t_f | Current fall time | | - | 0.8 | - | |
| t_c | Cross-over time | $V_{CC} = 480\text{ V}$, $I_C = 20\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 100\ \Omega$, $T_j = 125\text{ }^\circ\text{C}$ (see Figure 16: "Test circuit for inductive load switching") | - | 2.4 | - | ns |
| $t_r(V_{off})$ | Off voltage rise time | | - | 1.1 | - | |
| $t_{d(off)}$ | Turn-off delay time | | - | 2.4 | - | |
| t_f | Current fall time | | - | 1.2 | - | |

Table 8: Inductive load switching loss characteristics

| Symbol | Parameter | Test conditions | Min. | Typ. | Max. | Unit |
|-----------------|-------------------------|---|------|-------|------|------|
| $E_{on}^{(1)}$ | Turn-on switching loss | $V_{CC} = 480\text{ V}$, $I_C = 20\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 100\ \Omega$ (see Figure 18: "Switching waveform") | - | 0.84 | - | mJ |
| $E_{off}^{(2)}$ | Turn-off switching loss | | - | 7.4 | - | |
| E_{ts} | Total switching loss | | - | 8.24 | - | |
| $E_{on}^{(1)}$ | Turn-on switching loss | $V_{CC} = 480\text{ V}$, $I_C = 20\text{ A}$, $V_{GE} = 15\text{ V}$, $R_G = 100\ \Omega$, $T_j = 125\text{ }^\circ\text{C}$ (see Figure 18: "Switching waveform") | - | 0.86 | - | mJ |
| $E_{off}^{(2)}$ | Turn-off switching loss | | - | 11.5 | - | |
| E_{ts} | Total switching loss | | - | 12.36 | - | |

Notes:

⁽¹⁾ E_{on} is the turn-on loss when an external diode is used in the test circuit in [Figure 16: "Test circuit for inductive load switching"](#).

⁽²⁾Turn-off loss includes the tail of the collector current.

2.1 Electrical characteristics (curves)









Figure 8: Normalized breakdown voltage vs temperature




Figure 9: Gate charge vs gate-emitter voltage




Figure 10: Capacitance variations




Figure 11: Switching loss vs gate resistance




Figure 12: Switching loss vs temperature







Figure 13: Switching loss vs collector current






3 Test circuits

Figure 16: Test circuit for inductive load switching




AM01504v1

Figure 17: Gate charge test circuit



AM01505v1

Figure 18: Switching waveform



AM01506v1

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of ECOPACK® packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

4.1 TO-220FP package information

Figure 19: TO-220FP package outline




Table 9: TO-220FP package mechanical data

| Dim. | mm | | |
|------|------|------|------|
| | Min. | Typ. | Max. |
| A | 4.4 | | 4.6 |
| B | 2.5 | | 2.7 |
| D | 2.5 | | 2.75 |
| E | 0.45 | | 0.7 |
| F | 0.75 | | 1 |
| F1 | 1.15 | | 1.70 |
| F2 | 1.15 | | 1.70 |
| G | 4.95 | | 5.2 |
| G1 | 2.4 | | 2.7 |
| H | 10 | | 10.4 |
| L2 | | 16 | |
| L3 | 28.6 | | 30.6 |
| L4 | 9.8 | | 10.6 |
| L5 | 2.9 | | 3.6 |
| L6 | 15.9 | | 16.4 |
| L7 | 9 | | 9.3 |
| Dia | 3 | | 3.2 |

5 Revision history

Table 10: Document revision history

| Date | Revision | Changes |
|-------------|----------|---|
| 17-Dec-2004 | 2 | New template, no content change |
| 05-Aug-2005 | 3 | Some values changed in table 6 |
| 02-Dec-2015 | 4 | Text and formatting changes throughout document On cover page: - updated Title, Features and Description Added Electrical ratings section heading In section Electrical ratings: - updated tables Absolute Maximum ratings and Thermal Data In section Electrical characteristics: - updated table Static characteristics Added section Package information Updated TO-220FP package information |

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2015 STMicroelectronics – All rights reserved