

Cable gland - G-INS-M63-L68N-NNES-S - 1411169

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 34 mm ... 44 mm, Shielding: No, Connecting thread: M63, Color: silver

The illustration shows version G-INS-M25-M68N-NNES-S



Key Commercial Data

Packing unit	1 pc
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	65 mm
Wrench size, union nut	64 mm
Wrench size, support	68 mm
Hexagon angular dimension GRP	70 mm
Length of the connecting thread	14 mm
Feed-through hole diameter	63.1 mm ... 63.3 mm
External cable diameter	34 mm ... 44 mm

Ambient conditions

Degree of protection	IP69K
	IP68 (5 bar, 30 min.)
	IP66
	4X
Ambient temperature (operation)	-20 °C ... 100 °C (static)

General

No. of conductors	1
-------------------	---

Cable gland - G-INS-M63-L68N-NNES-S - 1411169

Technical data

General

Cable gland material	Brass, nickel-plated
Seal material	Neoprene
Cable seal material	Neoprene
O-ring material	NBR
Shielded	No
Thread type on connection side	M63
Torque	25 Nm (Union nut)
Color	silver

Classifications

eCl@ss

eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals


Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed 

Cable gland - G-INS-M63-L68N-NNES-S - 1411169


Approvals

cUL Listed 

cULus Listed 

Drawings

Dimensional drawing



Dimensional drawing