



CERTILOK - Die Set

0.3	0.5	1.5
0.35	0.75	2.5 4
0.5	1.0	
mm		

View X

Die set used with basic hand tool P/N 169400-0.  
See instruction sheet 408-6764

Spare contact locator available P/N 2-539785-4

Basis HDZG Basic Handtool	Profil Profile	Kontakt Contact	DGB (mm <sup>2</sup> ) Wire Range	ISO Ø INS. Range	Draht CH Wire CH ±0.05	Draht CW Wire CW
169400-0	1	964321	0.2-0.5	1.15-1.6	1.18	1.78
	1	969008	0.2-0.5	1.15-1.6	1.18	1.78
	2	964323	0.5-1.0	1.4-2.1	1.45	2.03
	2	964303	0.5-1.0	1.4-2.1	1.45	2.03
	3	964325	>1.0-2.5	2.2-3.0	1.8	2.79
	3	964305	>1.0-2.5	2.2-3.0	1.8	2.79
	4	964327	>2.5-4.0	3.3-4.5	2.35	3.30
	4	964307	>2.5-4.0	3.3-4.5	2.35	3.30

<small>THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISIONS.</small>		DRW K. Czech 07 JUL 98 CHK J. Reuter 10 JUL 98	Tyco Electronics AMP GmbH 64625 Bensheim (Germany)
DIMENSIONS: mm - 0.1 IN 7168m	TOLERANCES UNLESS OTHERWISE SPECIFIED: 0 PLC ±0.1 1 PLC ±0.1 2 PLC ±0.1 3 PLC ±0.1 4 PLC ±0.1 ANGLES ±0.5	NAME PRODUCT SPEC APPLICATION SPEC	Matrzensatz DIE SET (for SPT and TAB 4.8mm)
MATERIAL -	FINISH -	WEIGHT -	SIZE A3 CAGE CODE 00779 DRAWING NO. C=539615-1 RESTRICTED TO -
CUSTOMER DRAWING		SCALE 2:1	SHEET 1 of 1 REV A