



- .040 DIA HOLE IS RECOMMENDED FOR P.C. BOARD
- CONNECTOR MATES WITH ANY AMP 44 POSN RECEPTACLE
- REPLACEMENT PIN AMP# 207683-8
- UL/CSA DESIGNATION STAMPED IN THIS AREA.
- CLINCH NUT(QTY = 2) IS USED ON 208868-3 ONLY.
- FINISH: CADMIUM PER QQ-P-416
- FINISH: ZINC PLATED PER ASTM-B-633, .000200-.000400 THK WITH SUPPLEMENTARY CHROMATE (Cr3+)

PLATED PER 7	5-208868-1
5, PLATED PER 6	208868-3
PLATED PER 6	208868-2
PLATED PER 6	208868-1
DESCRIPTION	PART NO.

THIS DRAWING IS A CONTROLLED DOCUMENT.		DIN 1-7-88		Tyco Electronics Corporation	
DIMENSIONS: INCHES		C.C. THOMAS 1-26-88		Harrisburg, Pa 17105-3608	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		CHK F.C. BALLEW III		NAME	
0 PLC ± -		APVD		PRODUCT SPEC	
1 PLC ± -		NAME		APPLICATION SPEC	
2 PLC ± -		SIZE		RESTRICTED TO	
3 PLC ± .005		A1		00779 C=208868	
4 PLC ± -		CUSTOMER DRAWING		SCALE 4:1 SHEET 1 OF 1 REV	
ANGLES ± -					
FINISH SEE CALLOUTS					