




# LRS180150

## High Bay Lighting Kit/ Heatsink Thermal Solution

### High Thermal Performance

#### Features

- Excellent thermal performance – large heatsink surface and lightweight
- High thermal conductivity aluminum alloy
- Thermal coating Technology – thermal radiation enhancement
- Fully mechanical components
- Optional E39/40 Connector



#### Applications

- LED Bay Lighting 100~150W

#### Description

The LRS series provides excellent thermal performance and design flexibility for LED lighting applications. The LRS series stamped heatsinks provide lower thermal resistance than traditional extruded, cold forged, and die-cast heatsinks. High aspect ratio fin provides excellent heat transfer capability. Various material finishes are available for enhanced thermal performance.

#### Ordering Information

Model	Finish	Option																
LRS180150	UF	K																
	↓	↓																
	<table border="1"> <thead> <tr> <th>Code</th> <th>Spec.</th> </tr> </thead> <tbody> <tr> <td>UF</td> <td>No Finish</td> </tr> <tr> <td>TW</td> <td>Thermal Coating White</td> </tr> <tr> <td>CB</td> <td>Commercial Anodizing Black</td> </tr> <tr> <td>CA</td> <td>Commercial Anodizing Clear</td> </tr> </tbody> </table>	Code	Spec.	UF	No Finish	TW	Thermal Coating White	CB	Commercial Anodizing Black	CA	Commercial Anodizing Clear	<table border="1"> <thead> <tr> <th>Code</th> <th>Spec.</th> </tr> </thead> <tbody> <tr> <td>Blank</td> <td>Heatsink only</td> </tr> <tr> <td>K</td> <td>Heatsink with Accessories and socket</td> </tr> </tbody> </table>	Code	Spec.	Blank	Heatsink only	K	Heatsink with Accessories and socket
Code	Spec.																	
UF	No Finish																	
TW	Thermal Coating White																	
CB	Commercial Anodizing Black																	
CA	Commercial Anodizing Clear																	
Code	Spec.																	
Blank	Heatsink only																	
K	Heatsink with Accessories and socket																	

### General

RoHS	Lead-Free. Fully compliant to RoHS Directive 2011/65/EU
Packaging :	Box
Storage Temperature:	-40°C to +150°C

### Performance & Mechanical

Part Number Examples	*Heat Dissipation	Dimension (mm) D x H	Fin Surface Area (cm <sup>2</sup> )	Weight (kg)	Kit Solution
LRS180150TW	150W	180 x 180	5800	0.9	
LRS180150TWK	150W	180 x 312	5800	1.4	Lens, Housing, Connector
LRS180150CA	150W	180 x 180	5800	0.9	
LRS180150CAK	150W	180 x 312	5800	1.4	Lens, Housing, Connector
LRS180150UF	130W	180 x 180	5800	0.9	
LRS180150U FK	130W	180 x 312	5800	1.4	Lens, Housing, Connector

\*Heat Dissipation and Thermal Resistance should be considered for reference only. Actual results may vary due to the LED configuration, the finish chosen, and the environment conditions.

### Mechanical Specifications

