

APPLICABLE STANDARD																												
RATING	OPERATING TEMPERATURE RANGE	-35°C TO +85°C (NOTES 1)	STORAGE TEMPERATURE RANGE	-10°C TO + 60°C																								
	VOLTAGE	50V AC	APPLICABLE CONNECTOR	DF17# (**)-*DS-0.5V (57)																								
	CURRENT	0.3A																										
<b>SPECIFICATIONS</b>																												
ITEM	TEST METHOD	REQUIREMENTS	QT	AT																								
<b>CONSTRUCTION</b>																												
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X																								
MARKING	CONFIRMED VISUALLY.		X	X																								
<b>ELECTRIC CHARACTERISTICS</b>																												
CONTACT RESISTANCE	100m A (DC OR 1000 Hz).	60mΩ MAX.	X	-																								
INSULATION RESISTANCE	100V DC.	500MΩ MIN.	X	-																								
VOLTAGE PROOF	150V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-																								
<b>MECHANICAL CHARACTERISTICS</b>																												
INSERTION AND WITHDRAWAL FORCES	MEASURED BY APPLICABLE CONNECTOR.	<table border="1"> <thead> <tr> <th>SIGNAL</th> <th>INSERTION FORCE (N)MAX</th> <th>WITHDRAWAL FORCE (N)MIN</th> </tr> </thead> <tbody> <tr><td>20</td><td>200</td><td>20</td></tr> <tr><td>30</td><td>300</td><td>30</td></tr> <tr><td>40</td><td>400</td><td>40</td></tr> <tr><td>50</td><td>500</td><td>50</td></tr> <tr><td>60</td><td>600</td><td>60</td></tr> <tr><td>70</td><td>700</td><td>70</td></tr> <tr><td>80</td><td>800</td><td>80</td></tr> </tbody> </table>	SIGNAL	INSERTION FORCE (N)MAX	WITHDRAWAL FORCE (N)MIN	20	200	20	30	300	30	40	400	40	50	500	50	60	600	60	70	700	70	80	800	80	X	-
SIGNAL	INSERTION FORCE (N)MAX	WITHDRAWAL FORCE (N)MIN																										
20	200	20																										
30	300	30																										
40	400	40																										
50	500	50																										
60	600	60																										
70	700	70																										
80	800	80																										
MECHANICAL OPERATION	50TIMES INSERTIONS AND EXTRACTIONS.	① CONTACT RESISTANCE: 60mΩ MAX. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
SHOCK	490 m/s <sup>2</sup> DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	① NO ELECTRICAL DISCONTINUITY OF 1μs. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
<b>ENVIRONMENTAL CHARACTERISTICS</b>																												
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ 5 TO 35→ 85→ 5 TO 35°C TIME 30→10 TO 15→ 30→10TO15min UNDER 5 CYCLES.	① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 500 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① CONTACT RESISTANCE: 60mΩ MAX. ② INSULATION RESISTANCE: 250 MΩ MIN. ③ NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-																								
CORROSION SALT MIST	EXPOSED IN 5% SALT WATER SPRAY FOR 48 h.	① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X	-																								
SULPHUR DIOXIDE	EXPOSED IN 10 PPM FOR 96 h. (TEST STANDARD:JEIDA-39)	① CONTACT RESISTANCE: 60 mΩ MAX. ② NO HEAVY CORROSION.	X	-																								
HEAT RESISTANCE OF SOLDERING	[RECOMMENDED TEMPERATURE PROFILE] 《SOLDERING AREA》 MAX250°C, 220°C FOR 60 SECONDS MAX. 《PREHEATING AREA》 150 TO 180°C 120 SECONDS. MAXIMUM TWICE ACTION IS ALLOWED UNDER THE SAME CONDITION. [RECOMMENDED MANUAL SOLDELING CONDITION ] SOLDERING IRON TEMPERATURE 350°C SOLDERING TIME : WITHIN 3 SECONDS.	NO DEFORMATION OF CASE OF EXCESSIVE LOOSENESS OF THE TERMINALS.	X	-																								
COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE																								
△																												
REMARKS		APPROVED	MO.NAKAMURA	05.05.20																								
NOTE1:INCLUDING THE TEMPERATURE RISE BY CURRENT.		CHECKED	TS.MIYAZAKI	05.05.19																								
UNLESS OTHERWISE SPECIFIED,REFER TO JIS C 0806.		DESIGNED	YH.MICHIDA	05.05.19																								
		DRAWN	YH.MICHIDA	05.05.19																								
Note QT:Qualification Test AT:Assurance Test X:Applicable Test		DRAWING NO.	ELC4-162140-06																									
SPECIFICATION SHEET		PART NO.	DF17A (4. 0)-*DP-0.5V (57)																									
HIROSE ELECTRIC CO., LTD.		CODE NO.	CL683	△ 1/1																								