

NOTES:

1. MATERIAL:
- A. HEADER HOUSING: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT ACC. UL 94 V0.
  - B. TERMINAL: TINBRONZE
  - C. WAFER: LIQUID CRYSTAL POLYMER 30% GLASS FLAME RETARDANT
2. PACKAGING ACCORDING EUR-14-005.
3. MARKING ACCORDING DWG 59550.
4. FOR MORE DETAILS REFER THE DRAWING 72844\_C (4 X6 SIGNAL SOFIX BOARD CONNECTOR)

5-ROHS: INFORMATIONS

- THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY REGULATIONS AS DESCRIBED IN GS-22-008.

- THE HOUSING WILL WITHSTAND EXPOSURE TO 260°C PEAK TEMPERATURE FOR 10 SECOND IN A WAVE SOLDER APPLICATION WITH A 1.6MM MINIMUM THICK CIRCUIT BOARD. SEE APPLICATION NOTES/PROCEDURES IF THEY ARE AVAILABLE. PACKAGING SPEC:GS-14-920.

Performance level	
72800-11YLF	Telcordia CO.
72800-21YLF	Telcordia CO.

www.fciconnect.com			surface 0.8 ISO 1302	tolerance std ISO 406 ISO 1101	projection MM		
			TOLERANCES UNLESS OTHERWISE SPECIFIED		size A3	Scale 3:1	
Dr	J.Taron	2004/11/19	ANGULAR	0.X ±0.3			
Eng	J.Taron	2004/11/19	LINEAR	0.XX ±0.15			
Chr	P.Legare	2004/11/19	0° ±2°	0.XXX ±0.05	ECN N11-0071		
Appr	P.Legare	2004/11/19	Product family	SOFIX	Spec ref RELEASE		
			title SOFIX 72 POS KIT		dvw no 72800		Rev. F
			SHIELDED HDR 3x24 STB		CUSTOMER		sheet 1 of 2
			catalog no				

rev	ecn no	dr	date
A	LS04-0342	JTA	2004/11/19
B	LS05-0021	JTA	2005-02-20
C	LS06-0084	LGO	2006-07-04
D	LS07-0195	JTA	2007-10-02
E	N09-0372	SH	2009-12-01
F	N11-0071	A.ZH	2011-03-23
-	-	-	-

Copyright FCI.

1

2

3

4

A

A

B

B

C


C

D

D

Product number								
Item	Rad Row	Number	Column					
			6	5	4	3	2	1
72800-X11LF	D	24	Q	Q	Q	Q	Q	Q
	C		P	P	P	P	P	P
	B		O	O	O	O	O	O
	A		N	N	N	N	N	N
72800-X12 LF	D	24	U	U	U	U	U	Q
	C		T	T	T	T	P	T
	B		S	S	S	S	S	S
	A		N	N	N	N	N	N
72800-X13 LF	D	12	Q	Q	Q	Q	Q	Q
	C							
	B		O	O	O	O	O	O
	A							

Item	DIM A
N	5.75
O	5.00
P	5.00
Q	5.00
R	5.00
S	5.75
T	5.75
U	5.75



Copyright FCI.

www.fciconnect.com		surface 0.8 ISO 1302 ✓	tolerance std ISO 406 ISO 1101	projection ⊕	MM ↔
TOLERANCES UNLESS OTHERWISE SPECIFIED					
Dr	J.Taron	2004/11/19	ANGULAR	0.X	±0.3
Eng	J.Taron	2004/11/19	LINEAR	0.XX	±0.15
Chr	P.Legare	2004/11/19	0° ±2°	0.XXX	±0.05
Appr	P.Legare	2004/11/19	Product family	SOFIX	Spec ref
FCI		Title		Rev.	
		SOFIX 72 POS KIT		72800	
		SHIELDED HDR 3x24 STB		F	
		catalog no		CUSTOMER	
				sheet 2 of 2	

REV F - 2006-04-17

1

2

3

4