



# PRODUCT SPECIFICATION

## PRODUCT SPECIFICATION OF THE 1.25MM CENTER FFC JUMPER CABLE (HIGH TEMPERATURE)

### *Revision List*

REVISION	MODIFICATION	SHEETS	DATE
A	First Release	1 - 5	2010/09/27
B	Updated Specification	1 - 5	2011/09/29
C	Modified Specification (Sections 2.2, 2.3, 6, 7)	1 - 5	2014/05/07

REVISION: <b>C</b>	ECR/ECN INFORMATION: EC No: <b>USW2014-0256</b> DATE: <b>2014/05/07</b>	TITLE: <b>PRODUCT SPECIFICATION 1.25MM CENTER FFC JUMPER CABLE (HIGH TEMPERATURE)</b>	SHEET No. <b>1 of 5</b>
DOCUMENT NUMBER: <b>PS-15268-001</b>	CREATED / REVISED BY: <b>M.IMIG</b>	CHECKED BY: <b>D.ENGLISH</b>	APPROVED BY: <b>S.FULTON</b>



# PRODUCT SPECIFICATION

## 1 SCOPE

This specification covers the 1.25mm center FFC (Flat Flexible Cable) jumper cable, high temperature style, using tin plated copper conductor.

## 2 PRODUCT DESCRIPTION

### 2.1 Product name and series number


Product name: 1.25MM CENTER FFC JUMPER CABLE (HIGH TEMP)

Product material no: 15268-XXXX

### 2.2 Dimensions, materials and markings

Product dimensions according SD-15268-001.

- Number of conductors ..... N: 3 to 79
- Pitch ..... P:  $1.25 \pm 0.10\text{mm}$
- Span ..... E:  $1.25 (N-1) \pm 0.15\text{mm}$
- Total width ..... W:  $1.25 (N+1) \pm 0.15\text{mm}$
- Margin width ..... M:  $1.25 \pm 0.20\text{mm}$
- Strip length ..... S:  $4.00 \pm 0.80\text{mm}$
- End thickness of the connection area .. Tc:  $0.30 \pm 0.05\text{mm}$
- Thickness of the insulated area ..... Ti:  $0.27 \pm 0.05\text{mm}$
- Insulated length ..... L: 20 to 60mm  $\pm 2.00\text{mm}$   
 61 to 100mm  $\pm 3.00\text{mm}$   
 101 to 200mm  $\pm 4.00\text{mm}$   
 201 to 3999mm  $\pm 5.00\text{mm}$   
 4000 to 5999mm  $\pm 10.00\text{mm}$   
 6000 to 9999mm  $\pm 15.00\text{mm}$
- Reinforcement length ..... F:  $8.00 \pm 2.00\text{mm}$
- End squareness ..... s-s': 0.40mm max.



REVISION: <b>C</b>	ECR/ECN INFORMATION: EC No: <b>USW2014-0256</b> DATE: <b>2014/05/07</b>	TITLE: <b>PRODUCT SPECIFICATION 1.25MM CENTER FFC JUMPER CABLE (HIGH TEMPERATURE)</b>	SHEET No. <b>2 of 5</b>
DOCUMENT NUMBER: <b>PS-15268-001</b>	CREATED / REVISED BY: <b>M.IMIG</b>	CHECKED BY: <b>D.ENGLISH</b>	APPROVED BY: <b>S.FULTON</b>



# PRODUCT SPECIFICATION

## 2.3 COMPOSITION

- Conductor: Material: Tin plated copper conductor  
Thickness: 0.10mm nominal (Standard)
- Insulation tape: Material: Polyester + Flame retardant adhesive  
Thickness: 0.086mm nominal  
Color: white
- Reinforcement tape: Material: Polyester + Adhesive  
Thickness: 0.15mm nominal  
Color: Blue

## 2.4 Safety agency approvals

Not applicable.

## 3 RATINGS

### 3.1 Current and applicable conductors

Cross section	Amps
0.08mm <sup>2</sup>	1.4

### 3.2 Temperature

Operating temperature: -40°C to +105°C

REVISION: <b>C</b>	ECR/ECN INFORMATION: EC No: <b>USW2014-0256</b> DATE: <b>2014/05/07</b>	TITLE: <b>PRODUCT SPECIFICATION 1.25MM CENTER FFC JUMPER CABLE (HIGH TEMPERATURE)</b>	SHEET No. <b>3 of 5</b>
DOCUMENT NUMBER: <b>PS-15268-001</b>	CREATED / REVISED BY: <b>M.IMIG</b>	CHECKED BY: <b>D.ENGLISH</b>	APPROVED BY: <b>S.FULTON</b>



# PRODUCT SPECIFICATION

## 4 PERFORMANCE

### 4.1 Electrical requirements

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
1	Conductor resistance	ASTM B 193	250 ohms/km MAXIMUM
2	Insulation resistance cond. to cond.	500 V DC	10 Mohms/km MINIMUM
3	Dielectric test	500 V AC for 1 minute	No disruptive discharge
4	Continuity test	3.0 V DC at 0.1mA	passed
5	Voltage rating		60 V AC MAXIMUM
6	Current rating	at 23°C increase in 10°C at the surface (all conductors under load)	1.4 A MIN

### 4.2 Physical requirements

ITEM	DESCRIPTION	TEST CONDITION	REQUIREMENT
7	Temperature rating		-40°C to +105°C
8	Heat resistance	168 hours at 136°C	Insulation resistance Dielectric test
9	Thermal shock	30 minutes at -55°C 5 minutes at +25°C 30 minutes at +85°C 5 minutes at +25°C	Insulation resistance after 25 cycles
10	Cold coiling	96 hours at -40°C / The sample will be wound on a 3mm dia. Mandrel	Insulation resistance Dielectric test Visual inspection
11	Wear by abrasion	Test following EN3475-503 Weight: 500g Speed: 60 cycles/min Abrasion tool: 0.13mm dia.	10000 cycles (standard) 1000 cycles (shielded) MINIMUM
12	Folding	The specimen shall be folded manually (Bending angle: 180° / Radius: 4mm)	20 times MINIMUM
13	Moisture resistance	96 hours at 60°C, 95% RH	Insulation resistance Dielectric test
14	Flame resistance	UL 758 VW-1	Passed
15	Solderability	Immersion of the area which is intended for soldering into a tin bath at 250 ± 10°C During 30 seconds	No delamination Solder reflow below 1 mm

REVISION:	ECR/ECN INFORMATION:	TITLE:	SHEET No.
<b>C</b>	EC No: USW2014-0256 DATE: 2014/05/07	<b>PRODUCT SPECIFICATION 1.25MM CENTER FFC JUMPER CABLE (HIGH TEMPERATURE)</b>	<b>4 of 5</b>
DOCUMENT NUMBER:	CREATED / REVISED BY:	CHECKED BY:	APPROVED BY:
<b>PS-15268-001</b>	<b>M.IMIG</b>	<b>D.ENGLISH</b>	<b>S.FULTON</b>



# PRODUCT SPECIFICATION

## 5 PACKAGING

According to MOLEX packaging specification: PK-15268-001

## 6 UL APPROVAL

Materials used and construction of cable are UL compliant under UL style 20706

Temperature rating: 105°C

Voltage rating: 60 V AC

## 7 ROHS COMPLIANCE

Cable construction is RoHS compliant

REVISION: <b>C</b>	ECR/ECN INFORMATION: EC No: <b>USW2014-0256</b> DATE: <b>2014/05/07</b>	TITLE: <b>PRODUCT SPECIFICATION 1.25MM CENTER FFC JUMPER CABLE (HIGH TEMPERATURE)</b>	SHEET No. <b>5 of 5</b>
DOCUMENT NUMBER: <b>PS-15268-001</b>	CREATED / REVISED BY: <b>M.IMIG</b>	CHECKED BY: <b>D.ENGLISH</b>	APPROVED BY: <b>S.FULTON</b>