


RECOMMEND P.C.B. LAYOUT



CIRCUIT SYMBOL CONTACT CONFIGURATION

SWITCH FUNCTION			
PDS. 1	PDS. 2	PDS. 3	
DN	NONE	DN	
2-3	OPEN	2-1	

- NOTES:
1. ALL DIMENSIONS IN MM
 2. GENERAL TOLERANCE: 0.0=±0.4 0.00=±0.25
 3. CONTACT RATING: 0.4(VA) max. @20VAC or DC max.
 4. FIXED TERMINAL & MOVING CONTACT: Cu alloy w/Au plate over Ni plate.
 5. ELECTRICAL LIFE: 30,000 make-and-break cycles at full load.
 6. INSULATION RESISTANCE: 1,000M Ohms min.
 7. DIELECTRIC STRENGTH: 1,000 V RMS @sed level.
 8. OPERATING TEMP.: -30°C to 85°C



A		10276	RELEASED FOR PRODUCTION	TITLE		400 MSP-1 R6/BLK VS2 R E				
REV.	ECN No.	DESCRIPTION		DATE	CHKD	SCALE	DATE	DR	BYG	REV
		THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSMITTED				2:1	7/14/99	MM	T411018	A