



- NOTE
1. MANUFACTURING PROCESS COULD LEAVE SCRATCH AND/OR PUNCH MARKS HAVING NO AFFECT ON THE PRODUCT PERFORMANCE.
 2. SIDE CUT CAN BE PROVIDED TO PREVENT CARRIER CURVE.
 3. 2000 PIECES PER REEL.
 4. LABEL AS SHOWN BELOW IS INDICATED.

HRS		INSPECTION 検査
CODE No. 品名コード	CL575-3232-6	
PART NO. 品名	FX16-31P-GNDL(A)	
QTY 数量	2,000 PCS	
PECULIAR 仕様		
Lot No		
SPLICE 継ぎ目		

5. DIMENSION IN () ARE FOR REFERENCE.
6. THIS IS A COMPONENT FOR SEPARATELY AVAILABLE PRODUCT:FX16-31P-0.5FCL OR FX16-31P-0.5SDL. WHEN FFC IS USED FOR THE CABLE, MAKE SURE TO USE WITH THE SPECIFIED COMBINATION.

NO.	MATERIAL	FINISH . REMARKS	1	STAINLESS	NO.	MATERIAL	FINISH . REMARKS	
UNITS mm		SCALE FREE	COUNT △	DESCRIPTION OF REVISIONS		DESIGNED	CHECKED	DATE
HRS HIROSE ELECTRIC CO., LTD.			APPROVED : HS. OKAWA	08.05.29	DRAWING NO.		EDC3-157550-00	
			CHECED : HT. YAMAGUCHI	08.05.28	PART NO.		FX16-31P-GNDL(A)	
			DESIGNED : TS. SHIBUYA	08.05.27	CODE NO.		CL575-3232-6-00	
			DRAWN : TS. SHIBUYA	08.05.27			△	