

APPLICATOR PARTS LIST

TYPE
SIDWISE **TERMI - FOIL**
CONTACT

AMP INCORPORATED
 HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.	NO.	DESCRIPTION	REQ.	PART NO.
1	WIRE CRIMPER	1	453946-2	42	GUARD MT.	1	8113061
2	INS. CRIMPER			43			
3	ANVIL	1	458906-2	44	SPRING - SHEAR	1	387083
4	ANVIL SPACER			45			
5	SHEAR FL FLOATING	1	689931-3	46			
6	REAR SHEAR PLATE	1	811239-1	47			
7	SHEAR BLADE SPACER			48			
8	FRONT SHEAR PLATE			49			
9	REAR ANVIL SPACER PLT.			50			
10	FRONT ANVIL SPACER PLT.			51			
11	TOOL SPACER	2	378246	52			
12	CRIMP SPACER			53			
13	FRONT STRIP GUIDE	1	692949-5	54			
14	REAR STRIP GUIDE	1	458908-1	55			
15	RAM	1	473699	56			
16	TOOL HOLDER			57			
17	ADJ. CRIMP MOUNT			58			
18	ADJ. BLOCK			59			
19	APPLICATOR MOUNT ASSY.			60			
20	BASE PLATE	1	465100-2	61			
21	BASE BLOCK	1	692793-2	62			
22	STRIP GUIDE PLATE	1	458910-1	63	BRACKET, AIR FEED SUP.	1	692036-1
23	ANVIL HOLDER	1	458909-1	64	1" AIR FEED	1	690021-1
24	AUX. ANVIL HOLDER	1	458907-1	65	TENSION ADJ. PL.	1	374999
25	STRIPPER	1	386361-1		MISCELLANEOUS		
26	STRIPPER MOUNT	1	386362	66	LUBRICATOR ASSY.	1	464519-2
27	RETAINER PLATE	1	389078	67	TERMINAL LUBRICANT	1	22014-1
28	STRIPPER MOUNT BRACKET	1	387715-1	68	SPREADER ASSY.	1	453596-1
29	STRIPPER BUSHING	1	389049-1	69	BRACKET, STOCK GUIDE	1	694927-4
30	STOCK DRAG	1	387650-4	70	EXTENSION, REEL BRKT	2	455807-2
31	STOCK DRAG HANDLE			71			
32	STOCK DRAG STUD	1	374900	72	BENDING FIXTURE ASSY	1	68196-1
33	STOCK DRAG SPRING	1	370572		REV. REVISION RECORD	DATE	BY ECN
34	STOCK DRAG ADJ. WASHER NUT	1	21022-3	A	REV. PER ECN	2-25-76	JG/RIS55
35	FEED FINGER HOLDER	1	386942	A1	INACTIVE	2-24-77	CE/R1983
36	FEED FINGER	1	473739-1	B	REACTIVATE W/CHANGES	8-17-81	CE/R4128
37	FEED FINGER TIP	1	387251	C	REV PER ECN	2-82	CE/100/4333
38	FEED FINGER SPACER			D	ECR-08-018679	7-08	TM
39	BASE CASTING	1	570238				
40	GUARD 457665-8	1	8113061				
41	GUARD BRACKET	1	8113061				

CRIMPING DATA				TERMINALS
TO APPLY TERMINAL				
WIRE SIZE	CRIMP HEIGHT			
12	.111			53644
10	.124			
CRIMP	SIZE	TYPE	FEED	
WIRE	.210	F		
INSUL.			.970	
SLEEVED				
INSULATION RANGE	WIRE RANGE			
W	12-10			
EXPLODED VIEW				
A-6089				
REMARKS				
⚠ REVERSE BRACKET 471799 (180°) ⚠ & REMOVE AIR PLUG FROM AIR CYL (LEFT REAR) MUST LAY WIRE IN BARREL ⚠ PRINT OF ASSY ITEM (72) MUST ACCOMPANY LOG SHEET ■ DENOTES WEARING PARTS (NO MINI) RECOMMEND PURCHASE REPLACEMENT				
THIS APPLICATOR IS TO BE USED ON				
AMP-O-LECTRIC 1-471273-2				DIST.
AMP-O-LECTRIC AIR FEED				4
SERIAL NO.		DATE SHIPPED		DESIGNED
				RUSS 7-23-73
				BENNETT
CUSTOMER NAME AND ADDRESS				CHK'D
				1/25-73
				APP'D
				7-25-73
APPLICATOR NUMBER	REV	D 566138-1		SHEET
				1 OF 1

FOR HARDWARE
 SEE 687524-2

THIS IS A CONTROLLED DOCUMENT
 AMP INCORPORATED HARRISBURG, PENNA.
 ALL RIGHTS RESERVED