



HAMMOND MANUFACTURING

1182E240
50/60Hz VA:50

PRI: 2x 117V BLK-WHT, BRN-ORN
SEC: 1x 240V @ 0.208A RED-BLU

1A0050A000A000240

MADE IN CANADA DATE PB

RoHS Compliant

CE RoHS

SUPPLIED WITH: TWO 0.062" T X 2.50" OD RUBBER WASHERS.
ONE 18GA X 2.375" OD STEEL MOUNTING WASHER.
ONE 10-24 BOLT 2.00" LONG WITH A LOCK WASHER AND 10-24 HEX NUT.

| ELECTRICAL DATA: | | |
|------------------|--------------------------------|---------------------|
| TESTS | CONDITIONS | ACCEPTANCE CRITERIA |
| Sec. N.L.V | @ 117V, 60Hz | |
| | BLK & BRN to WHT & ORN | |
| OR | @ 234V, 50Hz | |
| | BLK to ORN (Connect BRN & WHT) | |
| | RED - BLU | 271.52 V ±2% |
| POLARITY | BLK, BRN and RED. | ADDITIVE |
| DCR | BLK - WHT | 26.100 Ohms ±20% |
| IN OHMS | BRN - ORN | 26.100 Ohms ±20% |
| | RED - BLU | 64.400 Ohms ±20% |
| HI POT | PRIMARY - SECONDARY | 4000V, 60Hz, 1 SEC |
| | PRIMARY - PRIMARY | 600V, 60Hz, 1 SEC |

| | | | |
|--|--|--|---------------------------|
| PROPERTY AND COPYRIGHT NOTICE | | | |
| THIS DRAWING AND THE INFORMATION IT CONVEYS ARE THE PROPERTY OF HAMMOND MANUFACTURING. IT MAY NOT BE REPRODUCED, TRANSMITTED OR USED IN ANY MANNER WHATSOEVER WITHOUT THE WRITTEN PERMISSION OF HAMMOND MANUFACTURING. | | | |
| REV | NOTES | BY | DATE |
| 1 | UPDATED THE HARDWARE, WAS 8-32 X 1.75" LONG. | GG | 15/04/14 |
| | | ELECTRONIC DIVISION 52 RANKIN PLACE, WATERLOO, ONTARIO, N2J 3Z5 PHONE: 519.886.6181 FAX: 519.886.9540 | |
| TOROID POWER TRANSFORMER | | | |
| DRAWN G. GRAY | | DATE 21/03/2014 | NUMBER 1182E240 |
| APPROVED | | DATE | |