

APPLICABLE STANDARD					
RATING	OPERATING TEMPERATURE RANGE	-25°C TO +85°C	STORAGE TEMPERATURE RANGE	-25°C TO +60°C	
	VOLTAGE		APPLICABLE CABLE	CABLE DIAMETER : $\phi 6.4\sim 7.8$	
	CURRENT				
SPECIFICATIONS					
ITEM	TEST METHOD	REQUIREMENTS	QT	AT	
CONSTRUCTION					
GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X	
MARKING	CONFIRMED VISUALLY.		X	X	
	COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
REMARK			APPROVED	A0. SUZUKI	09.05.11
THIS PRODUCT SHALL BE MATED WITH DH30B-27S, IT APPLIES TO DH30B-27S ABOUT A MECHANICAL, ENVIRONMENTAL CHARACTERISTICS. Unless otherwise specified, refer to JIS C 5402.			CHECKED	KN. ICHIKAWA	09.05.11
			DESIGNED	MO. SHIMOYAMA	09.05.11
			DRAWN	MO. SHIMOYAMA	09.05.11
			Note QT:Qualification Test AT:Assurance Test X:Applicable Test		
	SPECIFICATION SHEET		PART NO.	DH-27-CT2B	
	HIROSE ELECTRIC CO., LTD.		CODE NO.	CL244-0048-8-00	1/1