

# HTZ260G Series

$I_{F(AV)} = 4.7 \text{ A}$   
 $V_{RRM} = 22400 \text{ V}$

# High Voltage Diode Rectifier Module

# LARONTROL

Electronic Devices

Type Number	Repetitive Peak	Minimum Avalanche Voltage $V_{(BR)R}$
HTZ260G22K	22400	23800
HTZ260G19K	19600	21000
HTZ260G16K	16800	18200
HTZ260G14K	14000	15400

CIRCUIT DIAGRAM

CURRENT RATINGS - AIR COOLED			
$I_{F(AV)}$	Mean forward current	Half wave resistive load $T_{amb} = 35^{\circ}\text{C}$	4.7 A
$I_F$	Continuous (direct) forward current	$T_{amb} = 35^{\circ}\text{C}$	5.8 A
$R_{th(j-a)}$	Thermal resistance junction to ambient		1.8 $^{\circ}\text{C/W}$
CURRENT RATINGS - OIL COOLED			
$I_{F(AV)}$	Mean forward current	Half wave resistive load $T_{oil} = 60^{\circ}\text{C}$	6.0 A
$I_T$	Continuous (direct) forward current	$T_{oil} = 60^{\circ}\text{C}$	7.5 A
$R_{th(j-o)}$	Thermal resistance junction to oil		0.97 $^{\circ}\text{C/W}$
SURGE RATINGS			
$I^2t$	$I^2t$ for fusing	10 ms half sine $T_{vj} = 150^{\circ}\text{C}$	200 $\text{A}^2\text{sec}$
$I_{FSM}$	Surge (non-repetitive) forward current	$T_{vj} = 150^{\circ}\text{C}$	200 A
TEMPERATURE AND FREQUENCY RATINGS			
$T_{vj}$	Virtual junction temperature	Forward (conducting)	180 $^{\circ}\text{C}$
		Reverse (blocking)	180 $^{\circ}\text{C}$
$T_{stg}$	Storage temperature range		-40 to 100 $^{\circ}\text{C}$
f	Frequency range		20 to 400 Hz
CHARACTERISTICS $T_{case} = 25^{\circ}\text{C}$ unless otherwise stated			
$V_{FM}$	Forward voltage	At 12 Amps peak	max 16 V
$I_{RM}$	Peak reverse current	At $V_{RRM}$ ; $T_{case} = 150^{\circ}\text{C}$	max 0.5 mA

<p><b>Dimensioned Outlines</b>                  Dimensions shown are maximum in mm</p> <p>Weight typ.: 1,7 Kg</p>		<p><b>ZG</b></p> <p>Issue 1 June 1998</p>
---	--	---

# HTZ260G Series

$$I_{F(AV)} = 4.7 \text{ A}$$

$$V_{RRM} = 22400 \text{ V}$$

# High Voltage Diode Rectifier Module

# LARONTROL Electronic Devices

