

COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE	COUNT	DESCRIPTION OF REVISIONS	BY	CHKD	DATE
△					△				
△					△				
<b>APPLICATION STANDARD</b>									
<b>RATING</b>	OPERATING TEMPERATURE RANGE	-55 °C TO +85 °C			STORAGE TEMPERATURE RANGE	— °C TO — °C			
	VOLTAGE	200V AC			OPERATING HUMIDITY RANGE	— % TO — %			
	CURRENT	2 A			APPLICABLE CABLE	AWG#26~36			
<b>SPECIFICATIONS</b>									
<b>ITEM</b>		<b>TEST METHOD</b>			<b>REQUIREMENT</b>			<b>QT</b>	<b>AT</b>
<b>CONSTRUCTION</b>									
GENERAL EXAMINATION		VISUALLY AND BY MEASURING INSTRUMENT.			ACCORDING TO DRAWING			X	X
MARKING		CONFIRMED VISUALLY						X	X
<b>ELECTRICAL CHARACTERISTICS</b>									
INSULATION RESISTANCE		500 V DC			1000 MΩ MIN.			X	—
VOLTAGE PROOF		650 V AC FOR 1 min.			NO FLASHOVER OR BREAKDOWN			X	—
<b>ENVIRONMENTAL CHARACTERISTICS</b>									
DAMP HEAT (STEADY STATE)		EXPOSED AT 40±2 °C, 90~95 %, 96 h.			1)INSULATION RESISTANCE: 1000 MΩ MIN. 2) NO DAMAGE, CRACK AND LOOSENESS OF PART.			X	—
RAPID CHANGE OF TEMPERATURE		TEMPERATURE-55→+15~+35→+85→+15~+35°C TIME 30→10~15→ 30 → 10~15 min. UNDER 5 CYCLES.			NO DAMAGE, CRACK AND LOOSENESS OF PART.			X	—
REMARKS				DRAWN	DESIGNED	CHECKED	APPROVED	RELEASED	
				<i>K. Kiriyama</i> 00.07.11	<i>T. Niisawa</i> 00.07.11	<i>H. Okawa</i> 00.07.11	<i>T. Yoshimura</i> 00.07.12		
UNLESS OTHERWISE SPECIFIED, REFER TO MIL STD 1344									
NOTE QT: QUALIFICATION TEST AT: ASSURANCE TEST X: APPLICABLE TEST									
<b>HRS</b> HIROSE ELECTRIC CO.,LTD.				<b>SPECIFICATION SHEET</b>			PART NO. <b>A3B-6D-2C</b>		
CODE NO.(OLD)		DRAWING NO.		CODE NO.		1		1	
CL		ELC4- 021393		CL 621 - 0306 - 0					

TO
PCK

