

Antenna - RAD-ISM-2459-ANT-FOOD-6-0-MCX - 2700674

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Dual band omnidirectional antenna with protection against vandalism; IP68 protection; frequency band/gain: 2.4 GHz/up to 6 dBi, 5 GHz/up to 8 dBi; EN 50155; temperature range: -40°C to +80°C; N (f) connection; 1 m long adapter cable, N (m) - MCX (m) connection.

Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	280.0 GRM
Custom tariff number	85177011
Country of origin	Switzerland

Technical data

Dimensions

Height	51 mm
Diameter	92 mm
Fixed cable length	1.00 m

Ambient conditions

Degree of protection	IP68
Ambient temperature (operation)	-40 °C ... 80 °C
Ambient temperature (storage/transport)	-40 °C ... 80 °C

General

With connecting cable	yes
Frequency range	2.4 GHz
	5 GHz
	2.4 GHz
	5.15 GHz ... 5.83 GHz
Horizontal beamwidth	360 °
Impedance	50 Ω
Gain	6 dBi (2.4 GHz, when mounted on metal surface)
	3 dBi (2.4 GHz, no metal surface)

Antenna - RAD-ISM-2459-ANT-FOOD-6-0-MCX - 2700674

Technical data

General

	8 dBi (5.6 GHz, when mounted on metal surface)
	5 dBi (5.6 GHz, no metal surface)
Wind velocity	160 km/h (Has a force of 10 N)
Connection method	N (female)
	SMA (male)
Cable type	EF 316
Fixed cable length	1.00 m
Bending radius, long-term	12.50 mm
Housing material	Aluminum, HRA 150
Assembly instructions	Protection class: IP68, only when mounted on a level surface

Classifications

eCl@ss

eCl@ss 4.0	27240409
eCl@ss 4.1	27240409
eCl@ss 5.0	27242215
eCl@ss 5.1	19070102
eCl@ss 6.0	27242208
eCl@ss 7.0	27242208

ETIM

ETIM 3.0	EC001423
ETIM 4.0	EC000416
ETIM 5.0	EC001698

UNSPSC

UNSPSC 6.01	20142601
UNSPSC 7.0901	20142601
UNSPSC 11	20142601
UNSPSC 12.01	20142601
UNSPSC 13.2	20142601