

APPLICABLE STANDARD				
RATING	OPERATING TEMPERATURE RANGE	-35 °C TO +85 °C(NOTE 1)	STORAGE TEMPERATURE RANGE	-10 °C TO +60 °C(NOTE 3)
	OPERATING HUMIDITY RANGE	40% TO 80%(NOTE 2)	STORAGE HUMIDITY RANGE	40% TO 70%(NOTE 3)
	VOLTAGE	250 V AC	CURRENT	AWG20 TO 22 : 3 A
				AWG24 TO 28 : 1 A
			AWG30 : 0.5 A	

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----

CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X

ELECTRIC CHARACTERISTICS

INSULATION RESISTANCE	500 V DC.	1000 MΩ MIN.	X	—
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	—

MECHANICAL CHARACTERISTICS

MECHANICAL OPERATION	30 TIMES INSERTIONS AND EXTRACTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
VIBRATION	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
SHOCK	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—

ENVIRONMENTAL CHARACTERISTICS

DAMP HEAT (STEADY STATE)	EXPOSED AT 40±2 °C, 90 TO 95 %, 96 h.	① INSULATION RESISTANCE: 500 MΩMIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—
RAPID CHANGE OF TEMPERATURE	TEMPERATURE -55→ 5 TO 35→85→ 5 TO 35°C TIME 30→ 5 → 30→ 5 min UNDER 5 CYCLES.	① INSULATION RESISTANCE:1000 MΩMIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	—

REMARKS

NOTE1:INCLUDING THE TEMPERATURE RISING BY CURRENT.
 NOTE2:NO CONDENSING.
 NOTE3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD AFTER PCBBOARD , OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERM STORAGE DURING TRANSPORTATION.

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
△				

Unless otherwise specified, refer to JIS C 5402.	APPROVED	TY. OMA	07. 02. 27
	CHECKED	HK. UMEHARA	07. 02. 27
	DESIGNED	AH. MIYAZAKI	07. 02. 22
	DRAWN	AK. MIURA	07. 02. 22

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-161939-01
--	-------------	----------------

HRS	SPECIFICATION SHEET	PART NO.	DF1E-*S-2. 5C
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL541
			△ 1/1