

## Contact insert module - HC-M-RJ45-AD-PC-M - 1419885


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Contact insert module, number of positions: RJ45, type : RJ45, Pin, 50 V, 1 A, application: Data, with adapter for patch cables



### Key Commercial Data

Packing unit	1 STK
GTIN	 4 055626 253237
GTIN	4055626253237

### Technical data

#### Dimensions

Height	50.7 mm
Width	34.2 mm
Length	14.6 mm

#### Electrical characteristics

Note	Use the patch cable from the accessories list.
Rated voltage (III/3)	50 V
Rated current	1 A
Rated surge voltage	0.8 kV
Connection profile	RJ45
Transmission characteristics (category)	CAT6

#### Ambient conditions

Ambient temperature (operation)	-25 °C ... 60 °C
---------------------------------	------------------

#### Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
-----------------------------	-------

#### General

Type	RJ45
------	------

# Contact insert module - HC-M-RJ45-AD-PC-M - 1419885

## Technical data

### General

Series	HC-M-RJ45
Color	light gray
Number of module slots	1
Flammability rating according to UL 94	V0
Degree of pollution	3
Overvoltage category	III

### Material data

Contact material	Copper alloy
Contact surface material	Au
Contact carrier material	PC

### Standards and Regulations


Flammability rating according to UL 94	V0
--	----

### Environmental Product Compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

## Drawings

Dimensional drawing



Male insert

## Approvals

Approvals

Approvals




CSA / UL Recognized / EAC

Ex Approvals

Approval details

## Contact insert module - HC-M-RJ45-AD-PC-M - 1419885

### Approvals

CSA		<a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a>	13631
UL Recognized		<a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a>	E118976
EAC			RU C- DE.AI30.B.01102

Phoenix Contact 2018 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>