

Protective covers - HC-B 24-SD-MQT/FS-AL - 1584567

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

HEAVYCON protective cover, type B24, for sleeve housing without double locking latch, with retaining cord, IP65, ALU



The illustration shows a protective cover in the B10 design

Key commercial data

Packing unit	1 PCE
Weight per Piece (excluding packing)	163.15 GRM
Custom tariff number	85389099
Country of origin	Germany

Technical data

Dimensions

Diameter of retaining cord eyelet	30 mm
-----------------------------------	-------

Ambient conditions

Degree of protection	IP65
Ambient temperature (operation)	-40 °C ... 125 °C

General

Design	B24
Type	for sleeve housing without double locking latch
Material	Aluminum, die-cast
Seal material	NBR
Locking latch material	High-grade steel, handle: PA-GF
Seal present	Yes
Assembly instructions	Not for HC-B...EMC housings
Connection	The guide pins of the protective cover must be removed when using coding sockets, pins, and bolts.

Protective covers - HC-B 24-SD-MQT/FS-AL - 1584567

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27143424
eCl@ss 5.1	27143424
eCl@ss 6.0	27143424
eCl@ss 7.0	27440209
eCl@ss 8.0	27440209

ETIM

ETIM 3.0	EC002314
ETIM 4.0	EC002314
ETIM 5.0	EC002314

UNSPSC

UNSPSC 6.01	30211817
UNSPSC 7.0901	39121416
UNSPSC 11	43172601
UNSPSC 12.01	39121522
UNSPSC 13.2	39121522