


NUT / Mutter
 2x nut M8, synthetic material
 p/n 4003003149
 DIN 934, ISO 4032
 Material Nylon-66
 2 x Kunststoffmutter M8,
 Art.-Nr.: 4003003149
 DIN 934, ISO 4032
 Material Nylon-66

CABLE / Kabel
 single wire AWG 24
 colour black
 UL-Style 1569
 Einzeldrhten AWG 24
 Farbe schwarz
 Betriebsspitzenspannung 500 V
 UL-Style 1569

MARKING / Aufdruck
 Production code
 EN60062/Factory code
 Produktionscode
 EN60062/Betriebstätte

CIRCUIT DIAGRAM
 Schaltbild



Tolerances acc. to DIN ISO 2768-m
 dimensions / Abmessungen (mm)

Magnetic properties	Conditions	Min	Typ	Max	Unit
Pull in	at 20 °C	92		146	AT
Test equipment		KMS-18 + PH 014			

Special Product Data	Conditions	Min	Typ	Max	Unit
Contact - form		NC/			
Contact rating	Any DC combination of V & A not to exceed their individual max.'s			10	W
operating voltage	DC or Peak AC			175	V
operating ampere	DC or Peak AC			0,5	A
Sensor-resistance	measured with 40% overdrive Sensor deactivated			290	mOhm
Housing material		Crastin,SK 645FR, rated 94V-0, 140 °C, E.I. Dupont			
Case color		black			
Sealing compound		Voltatex CE 12 FW-UL			

Environmental data	Conditions	Min	Typ	Max	Unit
Operating temperature	cable not moved	-30		80	°C
Operating temperature	cable moved	-5		80	°C
Storage temperature		-30		80	°C

Cable specification	Conditions	Min	Typ	Max	Unit
Cable typ		single wires			
Cable material		PVC			
Cross section [mm²]		AWG 24			

General data	Conditions	Min	Typ	Max	Unit
Mounting advice		over 5m cable, a series resistor is recommended.			
Tightening torque				1	Nm