



TEL: 973-328-3200 FAX: 973-328-31

DAFLEX Braided Fiberglass Sleeving UL VW-1

For High Temperature Applications to 1200°F

Description: Daflex D1200 sleeving is an extremely flexible, tightly braided class C fiberglass sleeving. It is non-flammable and treated for removal of all organic matter. The glass braid is fray resistant and non-corroding. It will provide maximum mechanical strength.

Dielectric strength determined by space factor.

It will not support combustion or fungus growth.

This series is RoHS compliant.

| DAFLEX Catalog No. | Size | Nom. I.D. | | Std. Spool or Coil |
|-----------------------|-------|-----------|-------|-----------------------|
| | | IN. | MM. | |
| D1200-24 | 24 | 0.022 | 0.56 | 100', 1000'* |
| D1200-22 | 22 | 0.027 | 0.69 | 100', 1000'* |
| D1200-20 | 20 | 0.034 | 0.86 | 100', 1000'* |
| D1200-18 | 18 | 0.042 | 1.07 | 100', 1000'* |
| D1200-17 | 17 | 0.047 | 1.19 | 100', 1000'* |
| D1200-16 | 16 | 0.053 | 1.35 | 100', 1000'* |
| D1200-15 | 15 | 0.059 | 1.50 | 100', 1000'* |
| D1200-14 | 14 | 0.066 | 1.68 | 100', 1000'* |
| D1200-13 | 13 | 0.076 | 1.93 | 100', 1000'* |
| D1200-12 | 12 | 0.085 | 2.16 | 100', 500'* |
| D1200-11 | 11 | 0.095 | 2.41 | 100'* |
| D1200-10 | 10 | 0.106 | 2.69 | 100', 500'* |
| D1200-9 | 9 | 0.118 | 3.00 | 100'* |
| D1200-8 | 8 | 0.133 | 3.38 | 100', 500'* |
| D1200-7 | 7 | 0.148 | 3.76 | 100'* |
| D1200-6 | 6 | 0.166 | 4.22 | 100', 500'* |
| D1200-5 | 5 | 0.186 | 4.72 | 100'* |
| D1200-4 | 4 | 0.208 | 5.28 | 100', 500'* |
| D1200-3 | 3 | 0.234 | 5.94 | 100'* |
| D1200-2 | 2 | 0.263 | 6.68 | 100', 500'* |
| D1200-1 | 1 | 0.294 | 7.47 | 100' |
| D1200-0 | 0 | 0.330 | 8.38 | 100' |
| D1200-3/8 | 3/8" | 0.387 | 9.83 | 100' |
| D1200-7/16 | 7/16" | 0.450 | 11.43 | 100' |
| D1200-1/2 | 1/2" | 0.512 | 13.00 | 100' |
| D1200-5/8 | 5/8" | 0.640 | 16.26 | 100' |
| D1200-3/4 | 3/4" | 0.768 | 19.51 | 100' |
| D1200-7/8 | 7/8" | 0.893 | 22.68 | 100' |
| D1200-1" | 1" | 1.018 | 25.86 | 100' |

* Preferred Put Up

Standard Color: Natural.

Applicable Specs:NEMA VS-1 1962. Class C, UL STD 1441.