

Crimp contact - IPCC 16-10-MT - 1733372

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Single crimp pin contact for flexible cable with 6 and 10 mm² cross section.

Product Features

- Simply snap into the VC-AR... panel cutout and you're done!
- No need for panel mounting flange
- Simply snap into the VC-AR... panel cutout and you're done!
- No need for panel mounting frame
- Crimp contacts are released using a flat-bladed screwdriver

Key Commercial Data

Packing unit	1 pc
Minimum order quantity	100 pc
Weight per Piece (excluding packing)	2.2 g
Custom tariff number	85366990
Country of origin	Germany

Technical data

Electrical characteristics

Rated current	50 A
Maximum load current	50 A

Ambient conditions

Ambient temperature (operation)	-40 °C ... 100 °C
---------------------------------	-------------------

Mechanical characteristics

Conductor cross section	10 mm ²
Stripping length of the individual wire	8 mm
Conductor cross section AWG max.	8
Insertion/withdrawal cycles	>= 25

General

Crimp contact - IPCC 16-10-MT - 1733372

Technical data

General

Series	VC-D
Connection method	Crimp connection

Material data

Contact surface material	silver-plated
--------------------------	---------------

Classifications

eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440204
eCl@ss 9.0	27440204

ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC002637
ETIM 5.0	EC000796

UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121409
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

Approvals

Approvals

Approvals

EAC / EAC / EAC

Crimp contact - IPCC 16-10-MT - 1733372

Approvals

Ex Approvals

Approvals submitted

Approval details

EAC

EAC

EAC
