


Date	SYM	REVISION RECORD	AUTH	DR.	CK.

NOTES:

MATERIAL:
 HOUSING : HIGH IMPACT NYLON 66, HALOGEN AND PHOSPHOR FREE
 UL94V-0, BLACK, UL FILE # E48285

RIVETS: BRASS, NICKLE PLATED.
 SPRING: 302 STAINLESS STEEL, NICKLE PLATED.
 WIRE: 24AWG, UL1007, CSA, TR64
 TEMPERATURE RANGE: -40°C TO +140°C
 RESISTANT TO SOLVENTS, COMMON OILS AND REFRIGERANTS

MOUNTING INSTRUCTION:
 USE 2-56 MACHINE SCREWS OR EYELETS 0.089" OD BY 0.15" FLANGE STIMPSON GS-3 SERIES OR EQUIVALENT. ALSO ADHESIVES AND DOUBLE SIDED TAPES WORK WELL.

Tolerance (Except as noted)	 Memory Protection Devices, Inc 200 Broad Hollow Road, Farmingdale, New York 11735	
decimal ±.5 (.020)	Scale	Drawn By B.S.
Fractional ± .8 (.030)	Title FOUR "AAA" CELL HOLDER	
Angular ± 3°	Date 10/18/03	Drawing Number BH4AAAW
		Approved By T.B.