

LARISA-O-CLIP8

~40° x 20° oval beam. Clip fastening for 0.8 mm thick PCB.


TECHNICAL SPECIFICATIONS:

Dimensions	9.9 + 9.9 mm
Height	7.5 mm
Fastening	clips
Colour	black
Box size	
Box weight	6.8 kg
Quantity in Box	10000 pcs
ROHS compliant	yes ⓘ



MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
LARISA-O	Lens	PMMA	clear
LARISA-HOLDER-CLIP8	Holder	PC	black




INDEX	PART NO	DESCRIPTION	MATERIAL	COLOUR
1	-	LARISA lens	PMMA	
2	C12907	LARISA-HOLDER-CLIP8	PC	black

Tolerances if not otherwise shown
According to DIN ISO 2768-1
Linear measures:
Up to 30mm class M, otherwise class C.
According to DIN ISO 2768-2
Form and position: class L

LEDiL

Ledil Oy
Salorankatu 10
FIN 24240 SALO
Finland

THIRD ANGLE PROJECTION:



DRAWING TITLE

LARISA-CLIP8

This drawing is the property of LEDiL Oy. It may not be reproduced, copied or communicated without a written agreement with LEDiL Oy.

SIZE PART NUMBER

A4


0,6 g

SHEET 1/1



PHOTOMETRIC DATA (MEASURED):





LED XB-D
FWHM 39.0 + 21.0°
Efficiency 79 %
Peak intensity 2.200 cd/lm
Required components:



LED XP-G
FWHM 39.0 + 25.0°
Efficiency 83 %
Peak intensity 2.050 cd/lm
Required components:



LED XQ-E
FWHM 40.0 + 17.0°
Efficiency 82 %
Peak intensity 2.800 cd/lm
Required components:




LED XQ-E HI
FWHM 41.0 + 14.0°
Efficiency 76 %
Peak intensity 3.500 cd/lm
Required components:



PHOTOMETRIC DATA (MEASURED):


LG Innotek

LED H35B0 (LEMWA32)
 FWHM 38.0 + 22.0°
 Efficiency 82 %
 Peak intensity 2.200 cd/lm
 Required components:





LG Innotek

LED H35C0 (LEMWA33)
 FWHM 39.0 + 27.0°
 Efficiency 81 %
 Peak intensity 1.840 cd/lm
 Required components:





LUMILEDS

LED LUXEON A
 FWHM 39.0 + 26.0°
 Efficiency 81 %
 Peak intensity 1.900 cd/lm
 Required components:



LUMILEDS


LED LUXEON Rebel
 FWHM 40.0 + 18.0°
 Efficiency 84 %
 Peak intensity 2.700 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):



LUMILEDS

LED LUXEON Rebel ES
 FWHM 39.0 + 25.0°
 Efficiency 82 %
 Peak intensity 2.000 cd/lm
 Required components:




LUMILEDS

LED LUXEON Rebel Plus
 FWHM 40.0 + 19.0°
 Efficiency 83 %
 Peak intensity 2.600 cd/lm
 Required components:





LUMILEDS

LED LUXEON Z
 FWHM 41.0 + 14.0°
 Efficiency 81 %
 Peak intensity 3.540 cd/lm
 Required components:



LUMILEDS


LED LUXEON Z ES
 FWHM 40.0 + 18.0°
 Efficiency 86 %
 Peak intensity 2.800 cd/lm
 Required components:




PHOTOMETRIC DATA (MEASURED):




LED NCSxx19A
 FWHM 41.0 + 19.0°
 Efficiency 81 %
 Peak intensity 2.250 cd/lm
 Required components:





LED NF2x757A
 FWHM 41.0 + 33.0°
 Efficiency 78 %
 Peak intensity 1.950 cd/lm
 Required components:



LED NF2x757G
 FWHM 42.0 + 25.0°
 Efficiency 76 %
 Peak intensity 1.530 cd/lm
 Required components:




LED NVSxx19A
 FWHM 40.0 + 24.0°
 Efficiency 79 %
 Peak intensity 1.850 cd/lm
 Required components:



PHOTOMETRIC DATA (MEASURED):



OSRAM
Opto Semiconductors

LED Duris S5 (2 chip)
FWHM 26.0 + 41.0°
Efficiency 85 %
Peak intensity 1.800 cd/lm
Required components:





OSRAM
Opto Semiconductors

LED Oslon Square EC
FWHM 40.0 + 22.0°
Efficiency 78 %
Peak intensity 1.950 cd/lm
Required components:




OSRAM
Opto Semiconductors

LED Oslon SSL 150
FWHM 39.0 + 19.0°
Efficiency 84 %
Peak intensity 2.900 cd/lm
Required components:



OSRAM
Opto Semiconductors

LED Oslon SSL 80
FWHM 40.0 + 17.0°
Efficiency 77 %
Peak intensity 2.530 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)